Technical Data Sheet

97 WAX / GREASE REMOVER

JUNE 2005

Solvent Blend

Product Data

Blended solvent for the removal of wax, grease and other surface contaminants prior to painting or pre-treating. Can be used on metals, FRP/GRP, certain plastics and existing paintwork. Not as aggressive as 87 Allsol, therefore more suitable for use on existing paintwork.

May be too aggressive on fresh lacquer – suggest using a weak solvent such as Mineral Turps.

Packaging:

Available 4L, 20L

Product Specifications:

Appearance: Clear Liquid Specific Gravity: 0.79 Flash Point: Below 0 deg C.

Health and Safety

Avoid breathing vapour. Use with adequate ventilation. High concentrations of vapour may cause headache or nausea, affect the nervous system and respiration.

Do not use in the presence of naked flame or other sources of ignition. Store away from heat.

Wear safety glasses / goggles, a half face respirator with organic vapour cartridge and PVC or nitrile chemical handling gloves.

Store / dispose of residues in accordance with local body regulations.

First Aid

If poisoning occurs, contact a doctor. The Poisons Information Centre may be of assistance – telephone 0800 POISON, 0800 764 766.

If swallowed, do NOT induce vomiting. Give a glass of water to drink and get medical attention urgently.

If affected by vapour, get into fresh air immediately.

If splashed into the eyes, flush them with copious quantities of clean water for 15 minutes and get urgent medical attention.

If splashed onto skin, wash with soap and water.

For further information, refer to the Material Safety Data Sheet for this product.

Spills / Disposal

Extinguish naked flames and avoid sparks. Absorb with sand, sawdust or earth. Collect in drums and arrange for disposal by a competent contractor, in accordance with local regulations.

Fire

Flammable liquid. Vapours from explosive mixture with air. Extinguishing media: foam, dry powder, CO2, water fog.

Do not use water, except as a fog to cool nearly containers.

Wear breathing apparatus when fighting fire.

Technical information given verbally or in writing is based on knowledge and research, given in good faith and believed to be reliable, but no guarantee of accuracy is made or implied. Since methods and conditions of use are beyond our control, all merchandise is sold and received subject to the condition that our liability whether express or implied for any defect in quality, or for any lack of fitness for the specified use thereof, is limited to the return of the purchase price if written claim is made within 14 days from date of delivery. It is recommended that the user makes his or her own tests to determine the suitability of the product for his own requirements. Freedom from patent restrictions is not implied.